



VpCI® EMITTING SYSTEMS & ELECTRONIC PRODUCTS



VpCI®-111 Emitter, Patented



PRODUCT DESCRIPTION

VpCI®-111 emitters are unique devices designed to provide corrosion protection for metal components and parts enclosed in non-ventilated control boxes, cabinets or tool boxes up to 11 cubic feet (312 liters). The Vapor phase Corrosion Inhibitor (VpCI®) emits vapors, which form a molecular layer on internal metal surfaces to protect critical, complex, and expensive electronic equipment during operation, shipping, or storage. VpCI®-111 is patented with a breathable Tyvek® membrane cover through which corrosion inhibitors are slowly released. VpCI®-111 provides long term protection against corrosion even in the presence of adverse conditions including salt, moisture, airborne contaminants, H₂S, SO₂, NH₃, and others.

*Tyvek is a registered trademark of DuPont™

TYPICAL APPLICATIONS

- Operating, packaged, and stored electrical equipment
- Marine navigation and communication equipment
- Aerospace electrical controls
- Electric motors
- Switching equipment
- Fuse boxes and power boxes
- Medical equipment
- Electrical wireways and terminal boxes
- Scientific and measuring instruments
- Telecommunications equipment and remote electronics devices

FEATURES

- Economical to use
- Provides continuous protection for up to 24 months during operation and/or shutdown
- Effective in polluted and humid environments
- Does not interfere with electrical, optical, or mechanical performance
- Multimetal protection
- Quick and easy installation
- Very convenient to install
- Non-toxic and safe to handle
- Compact and space-saving
- Free of nitrites, halogens, and phosphates
- No spraying, wiping, or dipping required
- VOC values meet Southern California Clean Air Act and other National and local regulations
- Self-stick back
- Self-stick date label
- NSN# 6850-01-408-9025
- Accepted by FDA for corrosion protection of electrical and electronic equipment within food processing plants
- Canadian Food Inspection Agency acceptance for indirect food contact
- Approved for U.S. military and NATO
- Product contains powder that is a commercial equivalent to MIL-1-22110C
- IBM approval # 44V5421



METHOD OF APPLICATION

VpCl[®]-111 is extremely simple and convenient to install. VpCl[®]-111 emitters should be installed as early as possible, preferably during manufacturing or assembly. Simply select a space within enclosed device where corrosion protection would be useful. Verify that the surface on which the device will be installed is clean and free of debris. Peel off the protective peel strip from the bottom of the device and attach it to the clean surface. The peel strip can be separated to reveal a self-adhesive sticker on which the installation and replacement dates can be noted. VpCl[®]-111 emitters can be installed in any position. For volumes greater than 11ft³ (312 L), install more than one VpCl[®]-111. If the enclosure is not totally air-tight or if the access doors are opened frequently, replace the VpCl[®]-111 emitter more often than every two years. After periods of heavy maintenance, replace the emitter. For additional protection, spray the enclosure very lightly with ElectriCorr[®] VpCl[®]-238.

PROPERTIES

Appearance	Green cup with Tyvek [®] lid
Protection	11 ft ³ (312 Liters) emitter
Standard size	Plastic device cup with breathable membrane 2.25 in. diameter x 1.27 in H (5.7 cm x 3.2 cm)

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT SAFETY DATA SHEET FOR MORE INFORMATION

PACKAGING AND STORAGE

Products should not be exposed to temperatures of over 185°F (85°C). VpCl[®]-111 is available in 10 individually wrapped emitters per carton.

STANDARD TEST METHODS

NACE TM0208-2008	Vapor Inhibiting Ability
NACE RP0487-2000	Selection of Rust Preventives
MIL-I-22110C	Vapor Inhibiting Ability

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec[®] Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec[®] Corporation warrants Cortec[®] products will be free from defects when shipped to customer. Cortec[®] Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec[®] Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec[®] Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.
BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE,

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec[®] Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC[®] CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
<http://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 01/30/17. Supersedes: 01/23/14 ©Cortec Corporation 2002-2017 of Cortec Corporation.
All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2017, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.

Distributed by: